

**Falls**

Model  
**IM3000**

# POSTLESS DIRECT HYDRAULIC WING FOR CATERPILLAR MOTOR GRADERS

*Get maximum visibility with  
the rugged Falls IM3000  
Postless Direct Hydraulic Wing.*



- 20" front lift height for higher benching
- Spring-loaded outer lift arm
- 12 and 14 ft. models available
- Ripper mount available
- Manually telescoping push arm
- Nitrided cylinders for increased corrosion resistance
- Adds less than 3,800 lbs. (12' model)
- Free factory installation (see ordering info)



# Falls SPECIFICATIONS

SPECIFICATIONS	IM3012	IM3014
Overall length	12' 6" (3.843 m)	14' 6" (4.45 m)
Moldboard thickness	7 gauge (2.38 mm)	
Moldboard height, front	36" (.91 m)	
Moldboard height, rear	36" (.91 m), optional: 32" (.81 m)	
Cutting edge (AASHO & carbide punched) (12.67 mm x 152 mm x 3.05 m)	1/2" x 6" x 12' (12.67 mm x 152 mm x 3.05 m)	(2) 5/6" x 6" x 7'
Average height under raised moldboard: Front	20" (.508 m)	
Rear	108" (2.745 m)	
Push bar	One (1) spring-cushioned telescoping	
Weight of moldboard only	950 lbs. (432 kg)	1,100 lbs. (500 kg)
Weight of moldboard and mountings	3,800 lbs. (1,721 kg)	3,925 lbs. (1,778 kg)

**Required valves:** Standard snow wing requires two (2) double-acting control valves.

YOUR DEALER IS:

**Specifications are subject to change without notice.**

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

*Falls® is a trademark of Little Falls Machine, Inc.  
Little Falls Machine, Inc. is an equal opportunity employer.*

0309-250-RP



## LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South  
Little Falls, MN 56345  
Toll-free 800-772-PLOW

Phone (320) 632-9266 • Fax (320) 632-3484

[www.fallsplovs.com](http://www.fallsplovs.com)