

Falls
SDL Series

DIRECT HYDRAULIC SNOW WING



- 8, 9, 10, 11, and 12 ft. Cutting Edge Lengths
- 3.5" Diameter Double-Acting Hydraulic Cylinders
- Nitrided Cylinders for Increased Corrosion Resistance
- 1-3/4" Wing Hinge Bolt
- Trip Edge or Trip Moldboard Available
- Equipped with Falls' Exclusive Wing Lock Valve with Built-In Relief
- Double-Boxed Wing Construction Eliminates Twisting
- Two (2) Cylinder Control for Precise Positioning
- Heavy-Duty Construction Throughout
- Works in Conjunction with Underchassis Scraper to Eliminate Windrows
- Shown with Optional Nitrogen-Accumulated Hydraulic Push Bar Extension

Falls SPECIFICATIONS

MODEL	SDL-9A	SDL-10A	SDL-11A
Overall length	9'6"	10'6"	11'6"
Overall height, front	30"		
Overall height, rear	30"		
Moldboard thickness	10 gauge hi-tensile steel, A607-50		
Cutting Edge (AASHO Punched)	1/2" x 6" x 9ft	1/2" x 6" x 10ft	1/2" x 6" x 11ft
Push Bar	One (1) adjustable spring-cushioned – Hydraulic extension optional		
Clearing width	60" - 90"	70" - 100"	80" - 110"
Front lift height	13"		
Rear lift height	96"	102"	108"
Weight, wing only	580 lb	640 lb	700 lb
Weight, wing & mtgs	1550 lb	1610 lb	1670 lb

Valves required: Two (2) double-acting hydraulic control valves.

Options available: Trip edge; nitrogen-accumulated hydraulic push bar extension.

YOUR DEALER IS:

Specifications are subject to change without notice.

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

*Falls® is a trademark of Little Falls Machine, Inc.
Little Falls Machine, Inc. is an equal opportunity employer.*

0309-250-RP



LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South

Little Falls, MN 56345

Toll-free 800-772-PLOW

Phone (320) 632-9266 • Fax (320) 632-3484

www.fallsplovs.com