

**Falls**  
Series 2000

# SERIES 2000<sup>TM</sup> TALL POST DIRECT HYDRAULIC WING FOR CATERPILLAR MOTOR GRADERS

*Get higher benching and smoother lift with the Falls Series 2000 Tall Post Direct Hydraulic Wing.*



- 60" front lift height for higher benching
- Improved front slide
- Spring-loaded outer arm lift
- 12 and 14 ft. models available
- Reduced moldboard interference
- Hydraulically elevated rear slide arm available
- Hydraulically telescoping push arm available
- Adds only 3,100 lbs. to grader (12' model)
- Free factory installation (see ordering info)

# Falls SPECIFICATIONS

| SPECIFICATIONS                               | 2012   | 2014   |
|--|--|--|
| Overall length                               | 12' 6" (3.843 m)                                       | 14' 6" (4.45 m)                                    |
| Moldboard thickness                          | 8 gauge (2.72 mm)                                      |  |
| Moldboard height, front                      | 36" (.91 m)  |  |
| Moldboard height, rear                       | 36" (.91 m), optional: 32" (.81 m)                     |  |
| Cutting edge (AASHO & carbide punched)       | 1/2" x 6" x 12'<br>(12.67 mm x 152 mm x 3.05 m)        | (2) 5/6" x 6" x 7'<br>(12.67 mm x 152 mm x 3.05 m) |
| Average height under raised moldboard: Front | 60" (1.525 m)  |  |
| Rear   | 104" (2.643 m)   |  |
| Push bar                                     | One (1) spring-cushioned telescoping with safety shear |  |
| Weight of moldboard only                     | 950 lbs. (432 kg)                                      | 1,100 lbs. (500 kg)                                |
| Weight of moldboard and mountings            | 3,100 lbs. (1,409 kg)                                  | 3,300 lbs. (1,500 kg)                              |

**Required valves:** Standard snow wing (manual rear slide adjustment) requires two (2) double-acting control valves.

Optional hydraulic rear slide adjustment requires an additional double-acting control valve. Required valves may be acquired through your motor grader manufacturer or through Little Falls Machine Inc. Please inquire.

**Available options:** Hydraulic slide adjustment (add 200 lbs). Hydraulic push bar extension (add 150 lbs). Ripper-mounted push bar.

YOUR DEALER IS:

**Specifications are subject to change without notice.**

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

*Falls® is a trademark of Little Falls Machine, Inc.  
Little Falls Machine, Inc. is an equal opportunity employer.*

1109-1M-RP



## LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South

Little Falls, MN 56345

Toll-free 800-772-PLOW

Phone (320) 632-9266 • Fax (320) 632-3484

[www.fallsplovs.com](http://www.fallsplovs.com)