

## alls Specifications

SPECIFICATIONS	2012	2014 14' 6" (4.45 m)	
Overall length	12' 6" (3.843 m)		
Moldboard thickness	8 gauge (2.72 mm)		
Moldboard height, front	36" (.91 m)		
Moldboard height, rear	36" (.91 m), optional: 32" (.81 m)		
Cutting edge (AASHO & carbide punched)	1/2" x 6" x 12' (12.67 mm x 152 mm x 3.05 m)	(2) 5/6" x 6" x 7' (12.67 mm x 152 mm x 3.05 m)	
Average height under raised moldboard: Front			
Rear			
Push bar	One (1) spring-cushioned telescoping with safety shear		
Weight of moldboard only	950 lbs. (432 kg)	1,100 lbs. (500 kg)	
Weight of moldboard and mountings	3,100 lbs. (1,409 kg)	3,300 lbs. (1,500 kg)	

Required valves: Standard snow wing (manual rear slide adjustment) requires two (2) double-acting control valves.

Optional hydraulic rear slide adjustment requires an additional double-acting control valve. Required valves may be acquired through your motor grader manufacturer or through Little Falls Machine Inc. Please inquire.

Available options: Hydraulic slide adjustment (add 200 lbs). Hydraulic push bar extension (add 150 lbs). Ripper-mounted push bar.

YOUR DEALER IS:		

## Specifications are subject to change without notice.

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

Falls® is a trademark of Little Falls Machine, Inc.

Little Falls Machine, Inc. is an equal opportunity employer.



## LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South Little Falls, MN 56345 Toll-free 800-772-PLOW Phone (320) 632-9266 • Fax (320) 632-3484 www.fallsplows.com