





- Free-Floating Front Toe
- Proven Design
- Requires Minimal Space
- 8, 9, 10, 11, and 12 ft. Cutting Edge Lengths
- 3.5" Diameter Double-Acting Hydraulic Cylinders
- Nitrided Cylinders for Increased Corrosion Resistance
- 1–3/4" Wing Hinge Bolt
- Trip Edge or Trip Moldboard Available
- Equipped with Falls' Exclusive Wing Lock Valve with Built-In Relief
- Double-Boxed Wing Construction Eliminates Twisting
- Two (2) Cylinder Control for Precise Positioning
- Heavy-Duty Construction Throughout
- Works in Conjunction with Underchassis Scraper to Eliminate Windrows
- Shown with Optional Nitrogen-Accumulated Hydraulic Push Bar Extension *with Rear Lift*

## Falls. SPECIFICATIONS

MODEL	SDL-9A	SDL-10A	SDL-11A
Overall length	9' 6"	10' 6"	11' 6"
Overall height, front	30"		
Overall height, rear	30"		
Moldboard thickness	10 gauge hi-tensile steel, A607-50		
Cutting Edge (AASHO Punched)	1/2" x 6" x 9'	1/2" x 6" x 10'	1/2" x 6" x 11
Push Bar	One (1) adjustable spring-cushioned – Hydraulic extension optional		
Clearing width	60" – 90"	70" – 100"	80" – 110"
Front lift height	13"		
Rear lift height	96"	102"	108"
Weight, wing only	580 lbs.	640 lbs.	700 lbs.
Weight, wing & mountings	1550 lbs.	1610 lbs.	1670 lbs.

Valves required: Two (2) double-acting hydraulic control valves.

**Options available:** Trip edge; nitrogen-accumulated hydraulic push bar extension.

YOUR DEALER IS:

Specifications are subject to change without notice.

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

Falls<sup>®</sup> is a trademark of Little Falls Machine, Inc. Little Falls Machine, Inc. is an equal opportunity employer.



Toll-free 800-772-PLOW Phone (320) 632-9266 • Fax (320) 632-3484 www.fallsplows.com