

Series 2000 SP



**View from Cab** 

Get better visibility, smoother lift and highperformance benching with the rugged Falls Series 2000™ SHORT POST Direct Hydraulic Snow Wing. Built exclusively for your Case Motor Grader.

(see ordering info)



## Falls. SPECIFICATIONS

SPECIFICATIONS	2012ASP	2014ASP	
Overall length	12' 6" (3.843 m)	14' 6" (4.45 m)	
Moldboard thickness	7 gauge (2.38 mm)		
Moldboard height, front	36" (.91 m)		
Moldboard height, rear	36" (.91 m), optional: 32" (.81 m)		
Cutting edge (AASHO & carbide punched)	1/2" x 6" x 12' (12.67 mm x 152 mm x 3.05 m)	(2) 5/6" x 6" x 7' (12.67 mm x 152 mm x 3.05 m)	
Average height under raised moldboard: Front Rear	40" (1.525 m) 104" (2.643 m)		
Push bar	One (1) spring cushioned telescoping with safety shear		
Weight of moldboard only	950 lbs. (432 kg.)	1,100 lbs. (500 kg.)	
Weight of moldboard and mountings	2,850 lbs. (1,293 kg.)	3,150 lbs. (1,429 kg.)	

**Required valves:** Standard snow wing (manual rear slide adjustment) requires two (2) double-acting control valves. Optional hydraulic rear slide adjustment requires an additional double-acting control valve.

Available options: Hydraulic slide adjustment (add 200 lbs). Hydraulic push bar extension (add 150 lbs). Ripper mounted push bar.

YOUR DEALER IS:		

## Specifications are subject to change without notice.

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

Falls® is a registered trademark of Little Falls Machine, Inc. Little Falls Machine, Inc. is an equal opportunity employer.



## LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South Little Falls, MN 56345 Phone 800-772-PLOW (320) 632-9266 Fax (320) 632-3484 www.fallsplows.com